

FSI B22

SELF-PROPELLED STUMP CUTTER WITH 2WD AND 14 HP ENGINE





SELF-PROPELLED

The hydraulic wheel drive enables effortless driving in terrain and up ramps. The direction of travel is controlled simply by turning a section of the handle.



OPERATOR-FRIENDLY

The vibration-damped and height-adjustable handle combined with the pivot-point design make it less strenuous for the operator to sweep the cutter arm from side to side.



ELECTRIC STARTER

Start the engine by the turn of a key. The reliable Kohler CH440 engine is easily started with the electric starter.



MAXIMUM POWER

By a simple and economical belt clutch the banded V-belt transfers the power from the engine to the FSI power-cut cutter wheel efficiently with minimal power loss.



SAFE TRANSPORT

With multiple, easy-accessible lashing and lifting points you can quickly fasten this stump cutter for transport and arrive safely to the next jobsite.

DATA SHEET







TECHNICAL DATA

ENGINE

| Engine | Kohler CH440 | |
|-----------------|-----------------|--|
| Engine size | 10.5 kW / 14 hp | |
| Cooling | Air | |
| Fuel | Petrol | |
| Tank capacity | 7 | |
| Cooling Fuel | Air Petrol | |

DRIVE SYSTEM

| Ground drive | 2WD |
|--------------|------------------------|
| Wheels | Ø410 x 110 - 4 ply |
| Brake | Manual- 2 x individual |

DIMENSIONS

| Length | 1700 mm |
|--------|---------|
| Width | 680 mm |
| Height | 1250 mm |
| Weight | 210 kg |

CUTTING HEAD

| Diameter | 386 mm |
|--------------------|----------------|
| Teeth/ Quantity | FSI 21 - 8 pcs |
| Clutch | V-belt |
| Cutter wheel drive | V-belt |
| Sweep | Manual |

WORK AREA

| Above ground level | 30 cm | |
|--------------------|------------------|--|
| Below ground level | 25 cm | |
| Sweep | 106 cm | |
| Max cutting depth | 2.1 cm per sweep | |

OPERATION

OPTIONAL

Document tube

Special color - (RAL color)

FEATURES

- Large wheels with individual hydraulic motors (2WD)
- Safety bar ensures the cutter wheel disengages upon release for increased operator safety
- Original FSI Teeth
- Bypass valve to disengage drive for freewheeling
- Electrical start of engine
- FSI power-cut specially designed cutter wheel for optimal capacity and durability
- Tool set

FSI Stump Cutters reserves the right to make changes in engineering, design, and specifications without notice. Dimensions may vary, depending on options and selections. Vers: 11 - 2023