# **Model overview**

JÄRNHÄST classic

JÄRNHÄSTEN

flex

flex 2

essence

NHASTEN

The Classic version, well known for both the huntsman and the forestry worker. The machine comes with standard tracks and can easily be equipped with different accessories which makes it an excellent partner in the forest.

A development of the Järnhästen with heavy duty tracks and movable accessory bracket for better manoeuvrability when having a trailer connected. The bracket is also used together with the timber grapple, tipper body etc. Hydraulic system as standard but can also be delivered without. The Järnhästen Flex would be the forestry worker and the arborist first choice.

New solutions and improvements have been implemented in the new Flex 2 for you with higher demands on simplicity, serviceability, and safety.

Now with radio-controlled, hydraulic winch for easier winching in rough terrain.

The front guard can easily be opened for new possibilities for both storage and increased access for maintenance work.

The top model in the range. A radio controlled and hydrostatic machine with powerful hydraulic suitable for different applications. The platform is movable during drive for the best centre of gravity enabling the best performance driving off-road or with various loads. Great opportunities for lots of accessories with all-around attachment. A machine for contractors but also suitable for Fire & Res-

cue, Arborists and Geotechnical engineers.

Visit lennartsforsplay on You Tube







# Flex

The machine is equipped either with Honda 9 or 13 Hp. It has up raised steering handle and transportation position. Max speed 7 km/h and 6,1 l fuel tank. Equipped as standard are double boggie, variator, forward/reverse gear, brake, diff lock, skidbar and Manual winch 10 meters and Heavy Duty Tracks. *Mechanical adjustment accessories Platform I* 

### Models

Part.no. 968 7461-00 IH2090 Flex I Weight 368 Kg

Part.no. 968 7461-15 IH20913 Flex I Weight 383 Kg



## **Flex Forest**

Machine is equipped either with Honda 9 or 13 Hp. Also up-raised steering handle with transport position. Top speed 7 km/h and 6,1 l fuel tank. Equipped as standard are double boggie, variator, forward/reverse gear, brake, diff lock, skidbar, anchor block, manual winch 10-meter wire, chainsaw bracket and furthermore equipped with felling bunk, loading guard and Power winch 20-meter wire with pull force of 7000/10 000 N and **Heavy Duty Tracks**. *Mechanical adjustment accessories platform(I) or Hydraulic adjusted + double valve incl. Hydraulic kit (HI)*. hydraulic flow 18 l/min and 140 Bar. <u>Models</u>

Part.no. 968 7461-21 IH2090 PW Flex I Heavy Duty Tracks Weight 450 Kg

**Part.no. 968 7461-23 IH2090 PW Flex HI Heavy Duty Tracks and Hydraulic** Weight 480 Kg

\*All above machines can be equipped with13 Hp














#### R/C Hydraulic winch for T1710 Part.no. 531 0170-00



Weight Speed Oil pressure Maximum pull strength Rec. Oil flow R/C Cable Range R/C 11 Kg 30 m/min 190 bar 500 Kg 10-15 l/min 2 channels 25m, 5 mm Ca 50 m

#### 2 Levers valve kit

#### Part.no. 531 0170-32

Valve kit consist of 2 levers for all movement except support legs and grip that has separately levers.



Crane 30 - 50

Reachable3.5 mLifting capacity 3,0m240 KgLifting capacity 1,2m500 Kg

Part. No. 531 0145-12



Work lights. LED 2 pcs 15W Part.no. 531 0145-13







#### **Timber Cart Combi**

#### Part.no. 531 0198-47

1210 mm

785 mm

1,8–3,8 m

155 Kg 16 x 6,5–8"

1000 Kg



The trailer is suspended pivotally on the Järnhästen and is extensible. All stakes are collapsible and boggie. Can also be equipped with Platform (5310135-40).

Width totally: Width between the Felling bunk: Extension of trailer min/max: Weight: Wheel: Loading capacity:

#### **Platform for the Timber Cart**

#### Part.no. 531 0135-40

The platform is delivered complete with fastening brackets. Sides and tailgate are foldable. The platform is made for the Timber Cart Combi (531 01 98-47)

Length:	200 cm
Height (side and tailgate):	30 cm
Width:	120 cm
Weight:	120 Kg
Loading capacity:	600 Kg



#### **Self-unloading Timber Cart**

#### Art. Nr. 501 4002-00

Unique terrain-characteristics. Easy to disassemble during transport. The Cart can be extended or shortened. Standing position when empty.

Length:	119 cm – 267 cm
Width between the Felling bunk:	92,5 cm
Width totally:	140 cm
Weight:	140 Kg
Loading capacity:	800 Kg

#### **Platform Classic Platform Flex**

ennartsfors

Part.no. 501 3984-02 Part.no. 501 3984-02-2

The platform is easily mounted on the Järnhästen. With the large tailgate lowered it is easy to load heavy materials from the ground with the help of the winch.

Length:	1180 mm
Width:	1020 mm
Height tailgate:	500 mm
Height sides:	290 mm
Weight:	72 Kg
Loading capacity:	500 Kg











#### **Platform Cart** Jointed platform Cart

#### Part.no. 531 0196-70 Part.no. 531 0196-70-1

The Platform Cart is suspended pivotally on the Järnhästen and the wheels are adjustable. When the wheels are in the low position it is ideally suited for rear loading with or without winch. The front side/ side board are fixed.


Length without wheels:	2150 mm
Width:	900 mm
Weight:	88 Kg
Length total:	2150 mm
Length w/o wheels	1730 mm
Wheel:	4,00–8"
Loading capacity	700 Kg

#### **Tipper body Classic Tipper body Flex HI**

#### Part.no. 531 0135-31 Part.no. 531 0142-64

The tipper platform is delivered complete with fastening brackets, could be used either manual, winch or hydraulic sides and tailgate are removable. With the sides and tailgate removed, the plat form is completely clean with no stakes in the corners. The front gate is not removable.

Length:	1080 mm
Width:	1070 mm
Height.	460 mm
Height sides:	290 mm
Weight:	60 Kg
Loading capacity	800 Kg



ennartsfors

Length:	1197 mm
Width:	1080 mm
Height.	750 mm
Weight:	75 Kg

#### Part.no. 531 0144-54









#### **Snatch block**

Part No. 531 0196-08

**The snatch block** is open with a swivel hook. Extremely useful in combination with the power winch, both for changing direction of pull and for winching the IronHorse forward.

#### Loading Plate Classic Loading Plate Flex I-model

#### Part No. 531 0135-15 Part No. 531 0144-08

Kit consisting of mounting brackets and plate. This kit makes it easy to load logs using the winch as the log's slides onto the machine. Foldable in a way that it can be in horizontal position when going without any load on the machine. The loading plate is also a support to the ground and work as a brake, so the machine doesn't move backwards. The loading plate is easy to mount on existing machine.

Dimension: 420 x 935 mm Weight: 25 kg



#### Loading Plate Flex HI-model Loading Plate Essence-model (Essence L-Plate not pictured)

Part No. 531 0142-87 Part No. 531 0155-94

Consisting of mounting brackets and plate easy to attach onto the fellingbunk. This kit makes it easy to load logs using the winch as the logs slides onto the machine. Foldable in a way that it can be in horizontal position when going without any load on the machine. The perfect combination together with the Hydraulic kit easily using the piston sliding on the logs.

Dimension: Weight: 780 x 740 mm 21 Kg









#### **Removable storage box**

Art. No. 531 0155-31

This newly developed storage box is made for your tools, petrol can, clothes or whatever you need. It is attached to the machine with hooks over the load cover and anchors to the machine with a simple snap fastener. Once in the forest, you can easily unload the box and make use of the entire load space for your needs. Its' smooth and tall design makes it also possible to drive with both load and box.

Length	75 cm
Width	21 cm
Back height	52 cm
Front height	42 cm
Weight	9 Kg



#### Loading crane

#### Part No. 501 3999-01

The loader can be fitted to each Järnhästen with power winch. The loader is complete with bracket to the power winch, adjustable loading arm, chains and roller.

Length loading arm (min/max): Weight:

850-1150 mm 50 Kg



#### Skidding Cart

#### Part.no. 531 0198-35

Perfect tool to attach behind The Järnhästen without leaving a scratch on the ground. Easy way to transport out the logs. Need Power winch to operate the skidder.

Weight:

38 Kg

















### Tracks for the Classic model

#### Part.no. 531 0000-01

Kevlar armed driving tracks, made or nature rubber and epoxy pin, casted into the rubber. The tracks have a very good tearing strength and hard-wearing. The tracks are special made for the Järnhästen

## Heavy Duty tracks for the Flex model

#### Part.no. 531 0141-40

The brand new track on the Flex Iron Horse is significantly longer life-spam and provide considerably better traction on ground and snow surface

## Spikes for the Classic tracks

Part.no. 531 0135-17

Mounting kit for the Driving tracks include 24 pieces for 2 Driving tracks, 12 spikes in each tracks. All are included in the kit, with screws, nuts and washers. The spikes have a toothed surface, as give a good grip in slippery and hard ground . 1 Spike, as spare, Part no. 531 01 41-84

#### Power winch IH 9 Hk & 13 Hk Power winch IH 9 Hk & 13 Hk\*

Part.no. 501 3998-05 Part.no. 531 0139-49

The Power winch to the Järnhästen include, a complete kit with 20 m. wire, corner block, pulley, belt, bar, and cover for the transmission. **\*For machines with intermediate drive shaft** 

Pulling force Cable Weight

drive shaft

700-1000 kp 20m, 6mm 70kg

Load Guard incl. left-/right bar

Part No. 531 0135-54-1

Part No. 531 0135-54

**Roller for Load Guard** 

Machine with intermediate

Part No. 501 4009-01









## Hand winch Heavy Duty Incl. bracket

#### Part.no. 531 0144-12

The Hand winch, included 20m 5mm wire, hook and bracket. 500 kg pulling force.

#### **Timber Grapple**

#### Part.no. 531 0143-20

The grapple fits The Järnhästen Flex with hydraulic kit. The Grapple makes it quicker and easier to move bigger logs or brushes.

Includes grip, piston, bar and attachment for Flex HI

#### Storage cover.

#### Part.no. 501 3979-02

Tailor made storage cover to protect the engine, steering lever and power winch when storing the Järnhästen outside.



#### Detachable Working Light LED 20W Incl. bracket

#### Part.no. 531 0143-91

Detachable, reloading LED-light incl. attachment for the Järnhästen. Use as working light, when driving in the terrain or place it in a suitable place when working in the forest.

High quality working light in aluminum, that runs by reloading battery. The Ball light can be adjusted in 2 stages 1000 lumen or 2000 lumen. When using option 2000 lumen it will operate for 3 hours and at 1000 lumen for approximately 7 hours.









#### Hydraulic kit 5,0 cm3 Classic and Flex H

#### Part.no. 531 0137-03

With this Hydraulic kit you can use a wide variety of equipment and tools together with your Järnhästen. The Hydraulic kit can only be assembled on the 9 & 13 Hp version of the Järnhästen.

Flow: Pressure: 18 l/min. 140 bar



#### Loading bracket

#### Part.no. 531 0140-67

Bracket that makes it easier to load the wild animal onto the platform. The head of the animal will be placed further up towards the engine and by this gives a better balance while driving in the terrain.



#### **Engine Cover**

#### Part.no. 531 0140-68

The cover protects engine and exhaust system from external obstacles and dirt.(Only 9 Hp models)

#### Frame for EUR-pallet Classic Frame for EUR-pallet Flex

#### Part.no. 531 0141-33 Part.no. 531 0143-35

Smart accessories for loading a EUR pallet on the Järnhästen. Adapted for loading and unloading with pallet forks. The pallet is completely level despite the J**ärnhästen** chassis leans back slightly.









#### Felling bunk with tow ball Classic, Flex och Essence

Part.no. 531 0135-24

**The Felling bunk** have folding bars as are possible to lock in two positions, as make it easy to load and unload big logs. The Felling bunk have ring on each side to fasten the strap and a felling function to unload the log.

Loading gap: Loading height: Loading capacity: 800 mm 300 mm 1000 Kg

#### Extension bar 1 pcs (red) Extension bar 1 pcs (black)

Part.no. 501 3994-01 Part.no. 501 3994-01-B

**The extension bar** can be used to extend the Felling bunk and increase the loading capacity. It can also be used to facilitate the loading both manual and with the winch. The extension bars also have attachment lug to attach the snatch block as can be used for winching

Length (mounted in the bar) Total length: 300 mm 370 mm





### SERVICE KIT for your Järnhästen

**Part.no. 531 0144-30 (2017–2018), part.no. 531 0144-30-1 from 2019 -** IH2090PW/IH2013PW Variator/drive belt, winch belt, spark plug, throttle, and brake wire

Service kit IH2090/IH2013 without Power winch (winch belt excluded) Part.no. 531 0144-31 (2017 - 2018), part.no. 531 0144-31-1 from 2019 -

#### Servicekit Flex 2 (9 Hk)

Art. Nr. 531 0144-30-3 Variator/drive belt, spark plug, throttle and brake wire, Air filter and return filter



