



TRACTEE 1800A



TRACTEE 1800A



TRACTEE 1800A for transport



- Sweeper to adapt on all vehicles, car, van, city works carrier...
- A design that allows rapid adaptation for emergency intervention on site.
- Travel speed up to 25 km/h. Sweeping speed from 5 to 10 km/h.
- 500 mm right/left brush side shift (by turning the drawbar right/left).
- Mechanical oscillation on the right and on the left complies with the road conformity.
- Removable bearing carrier which ensures a quick release of the brush.

#### Standard equipment

- Anti-projection guard.
- Height-adjustable jockey wheel.
- Hooking ball Ø 50 mm and Ø 68 mm ring.
- Mudguard.
- Spare wheel mounted on the sweeper.

#### Technical characteristics

MODEL	TOWED 1800A MECHANICAL
<i>Brush length</i>	1800 mm
<i>Brush diameter</i>	550 mm
<i>Hub</i>	Metal
<i>Brush fibre type</i>	Mixed (polypropylene/polyester)
<i>Right / left offset</i>	500 mm on the right and on the left
<i>Orientation</i>	Permanent 25°
<i>Oscillation</i>	+/- 8°
<i>Brushing speed</i>	5 to 10 km/h
<i>Dimensions (L x W x H)</i>	4,16 x 1,97 x 1,02 m
<i>Weight (without options)</i>	610 kg
<i>Coupling</i>	Commercial vehicles, vans, 4x4s, site machinery...
<i>Drive</i>	Mechanical through wheels
<i>Wheels (Number: 2)</i>	185/70 R13
<i>Travel speed</i>	25 km/h



TRACTEE 1800A

MODEL	£	Reference
<b>MECHANICAL TOWED 1800A</b> 1.80 wide - Mixed brush (polypropylene/polyester) - Automatic clutch release - Mechanical drive through the wheels - Side offset of 500 mm - Anti spatter guard - Coupling : hooking ball Ø 50 mm and ring Ø 42x68 mm	<b>10,230</b>	72067D
<b>OPTIONS</b>		
Watering Pressure with 2 tanks of 150 L and 6 sprayers	12V Electric pump	<b>2,025</b> 72094D
	24V Electric pump	<b>2,025</b> 72095D
Holder for spare brush with a hub and 36 brush rings		<b>1,035</b> 72068D
12 Volts / 24 Volts lighting kit		<b>940</b> 72070D
Specific painting		<b>165</b> 72009C
Mixed brush (Polyester/Polypropylene) Ø 550 mm with staples, value for 1 m		<b>265</b> 24F003