



XYLOCRIBLE 2 M



XYLOCRIBLE 4 m + buffering screener

+ Rabaud advantages

- 2 models with large sifting areas (L x W) : 2 x 1 m on XYLOCRIBLE 2 M. 4 x 1 m on XYLOCRIBLE 4 M.
- Rolls driven electrically or hydraulically.
- Wood screener loading by bucket or wood processor outcome conveyor.
- Square cam rolls to separate the waste from the logs.
- Underneath waste evacuation.
- Custom configuration.
- Option : 6 cubic meters volume buffering storer through metal laths conveyor.

Technical characteristics

MODELS	XYLOCRIBLE 2M	XYLOCRIBLE 4M
<i>Sifting area (L x W)</i>	2 x 1 m	4 x 1 m
<i>Number of cams</i>	6 square + 1 «round» cam roll	15 square + 1 «round» cam roll
<i>Netting width</i>		48 mm
<i>Disc thickness</i>		12 mm
<i>Rotation speed</i>		58 rpm
<i>Weight</i>	from 1300 kg	From 4000 kg

Standard equipment

- Front and side loading hopper on XYLOCRIBLE 4 M.
- Individual and offset lubricating system for chain bearings.
- Progressive start-up motion for electric version.
- Reverse gear on electric versions.



Specific conditions : Consult us



For more information, contact us on +33 (0)2 51 48 51 43



Specific conditions :
Consult us

	Price	Reference
MODELS		
XYLOCRIBLE 2 METERS Stationary version - Adjustable unloading height • ET : Electric drive 2.2 kW three-phase	1 17875.00	70239A
• ET + RADIO CONTROL : Electric drive 2.2 kW three-phase + radio control	2 19715.00	70237A
• PH : Hydraulic drive (25 L/min. oil flow)	3 16690.00	70240A
OPTIONS		
Fixed delivery chute (mounted on the screener) : 350 mm length	710.00	70241A
Adjustable delivery chute (mounted on the screener) : 750 mm length	985.00	70242A

	Price	Reference
MODEL		
BUFFERING UNIT WITH INCLINED LATH CONVEYOR + XYLOCRIBLE 2 METERS + RADIO CONTROL Stationary version - 3.17 m unloading height Electric drive 2.2 kW 3-phase for the screener and 3 kW three-phase + radio control for the storer	4 41350.00	70243A
OPTIONS		
Fixed delivery chute (mounted on the screener) : 350 mm length	710.00	70241A
Adjustable delivery chute (mounted on the screener) : 750 mm length	985.00	70242A
Inspection hatch for lath inclined conveyor	1965.00	70298A

	Price	Reference
MODELS		
XYLOCRIBLE 4 METERS • ET : Electric drive 4 kW three-phase	5 32145.00	70223A
• ET + RADIO CONTROL : Electric drive 4 kW three-phase + radio control	6 33920.00	70224A
• PH : Hydraulic drive (25 L/min. oil flow)	7 27800.00	70225A
SET UP TYPE > OBLIGATORY TO DETERMINE		
Stationary version with 1.30 m unloading height from the ground	3380.00	70229A
Stationary version with unloading height to define (1.30 m mini.) - Price for 1 m	3115.00	DIV702
Rolling version with axle + drawbar with foldable hook - 2.85 m unloading height	4725.00	70206A
On rails with 5 m translation	15870.00	DIV702
OPTIONS		
Adjustable delivery chute : 800 mm length	1060.00	70213A
Adjustable delivery chute : 1450 mm length	1215.00	70214A
Discharge conveyor for waste under sifter	Contact us	DIV702
8 m discharge conveyor with hydraulic distributor + hydraulic unit (on PH version)	Contact us	

	Price	Reference
MODELS		
BUFFER STORAGE BY STRAIGHT SLATTED BELT + XYLOCRIBLE 4 METERS • ET : 4 kW three-phase electric drive for screening machine and buffer storage unit	8 54825.00	70219A
• ET + RADIO CONTROL : Electric drive 4 kW - three-phase for the screener and 3 kW - three-phase for the storer + radio control	9 56545.00	70220A
SET UP TYPE > OBLIGATORY		
Stationary version with 1.17 m unloading height - Price for 1 m	2965.00	DIV702
BUFFERING UNIT WITH INCLINED LATH CONVEYOR + XYLOCRIBLE 4 METERS • ET + RADIO CONTROL : Electric drive 4 kW - three-phase for the screener and 3 kW - three-phase for the storer + radio control	10 61115.00	70276A
OPTIONS		
Adjustable delivery chute : 800 mm length	1060.00	70213A
Adjustable delivery chute : 1450 mm length	1215.00	70214A
Inspection hatch for lath inclined conveyor	1965.00	70298A



