POST PEELER

Semi-automatic post peeler ROBOPEL

2 YEARS WARRANTY



ROBOPEL 250



ROBOPEL 250



ROBOPEL 250

Rabaud advantages

- Semi-automatic peeler adaptable to 3-point tractor. 20 HP combined electric/hydraulic power unit (optional).
- Bark all types of wood: chestnut, acacia, oak... round.
- Peeling of wood from 40 to 250 mm in diameter.
- Wood feed speed can be adjusted : output 60 to 120 posts/h.
- Peeling quality can be adjusted by pressing the two sprockets against the wood.
- Great efficiency thanks to a disc fitted with 6 cutting knives. Knives can be re-sharpened.
- Two V-shaped pneumatic wheels hold the wood in place as it enters and exits the machine.
- Automatic release of drive rollers (optional).
- Chip evacuation blower with 360° swivel chute. Ideal for loading chips onto a trailer.

Technical characteristics

MODEL	ROBOPEL 250
Wood type	For any kind of wood species (special attention to resinous wood), round woods.
Minimum/maximum poste Ø	40 / 250 mm
Number of knives	6
Disc speed	1500 rpm
Work dimensions (L x W x H)	1,99 x 2,39 x 2,67 m
Transport dimensions (L x W x H)	-
Weight	585 kg
Coupling	Tractor 3-point linkage cat. n°2 with removable pins

Standard equipment

- Post support.
- Protection grid.
- Hydraulic set for speed and bark-peeling pressure.



6-knife disc

	Price	Reference
MODELS		
ROBOPEL 250 - Semi-automatic • Disc driven by **PTO 540 rpm** *(delivered with shaft)* Hydraulic movement driven by tractor hydraulic pump Advised Starting up	**20540.00**	75601A
OPTIONS ROBOPEL 250		
Hydraulic unit, pump 30 L/min, 40 L tank with oil *(delivered without shaft)*	**2820.00**	70187A
Mixed drive with electro-hydraulic unit 15 kW / 20 HP* and PTO 540 rpm (tractor)	**8775.00**	75607A
Roll post holder	**690.00**	75605A
Feet extension 200 mm	**285.00**	75617A
Automatic unlocking of intake rollers	**2395.00**	75615A
Automatic unlocking of intake rollers - Mixed drive	**4015.00**	75616A
SPARE PARTS		
ROBOPEL 250 cutting knife (unit price)	**120.00**	756015

** 50 A minimum - In case of plugging to power generator, please contact us.*