



NOTCHED roller




STANDARD loading deck



Loading deck with chains

- Suitable for XYLOG 410 and 420 handsets.
- Adjustable feet to optimize log loading on intake conveyors.
- The rollers are controlled by the feed belt to optimise log transport.
- Sturdy construction to allow heavy logs loading.



5 m chain loading platform

### Technical characteristics

MODELS	NOTCHED ROLLER	STANDARD	3 METER INFEEDECKS - 3 CHAINS	5 METER INFEEDECKS - 2 CHAINS	5 METER INFEEDECKS - 3 CHAINS
Chain length	-	1,47 m	3 m	5 m	
Chains numbers	-	-	3	2	3
Log separating deck	-	4	3		
Infeed rollers	-	-	4	3	4
Maximum weight	-	2000 kg	3000 kg	4950 kg	5000 kg
Dimensions (L x W x H)	0,97 x 0,40 x 1,00 m	2,47 x 2,13 x 1,32 m	4,29 x 2,53 x 1,59 m	6,24 x 2,53 x 1,59 m	
Adjustable feet	250 mm	200 mm	125 mm		
Weight	-	225 kg	845 kg	1100 kg	1150 kg



XYLOG 410 mounted on a "floor stand"

MODELS		Price	Reference
<b>Feeding notched roller</b> (with 2 hydraulic hoses with couplers)	for XYLOG 410	<b>2095.00</b>	71736B
	for XYLOG 420	<b>2095.00</b>	71714A
<b>Conveyor extension with 4 rollers</b> (with 2 hydraulic hoses)		<b>4885.00</b>	71759A
<b>Loading deck</b>	<b>1,47 M</b> Length (2 hydraulic hoses with couplers)	<b>SIMPLE</b> by gravity	<b>3775.00</b> 71702A
	<b>3 M</b> Length (4 hydraulic hoses with couplers)	with <b>3 CHAINS</b>	<b>11500.00</b> 71760A
	<b>5 M</b> Length (4 hydraulic hoses with couplers)	with <b>2 CHAINS</b>	<b>9540.00</b> 71724C
with <b>3 CHAINS</b>		<b>12695.00</b> 71736A	
Transport platform + 3 m chain loading platform with hydraulic set-up	for XYLOG 410	<b>32530.00</b>	71708C
	for XYLOG 420	<b>31545.00</b>	71729A