



XYLOCUT 310 PE



XYLOCUT 310 PE



XYLOCUT 310 PE



- Dual function : Combines grappling and cutting functions.
- Suitable for hydraulic excavators from 13 to 17 Tons.
- 310 mm cutting diameter.
- Cutting branches or undergrowth by hand (a difficult task with a chainsaw).
- Ideal for hardwood.
- Clear cut thanks to the blade mounted on a mobile support.
- Hydraulic tilting : +/- 90°.
- Safety in operation: high clamps for a strong hold of the tree after the cut and during transportation.

### Technical characteristics

MODEL	XYLOCUT 310 PE
<i>Coupling</i>	Excavator from 13 to 17 Tons
<i>Cutting Ø</i>	310 mm
<i>Knife width</i>	-
<i>Upper grip opening</i>	1100 mm
<i>Lower grip opening</i>	-
<i>Cutting power</i>	36 Tons at 270 bar / 45 Tons at 350 bar
<i>Tilting</i>	+/- 90° (180° amplitude)
<i>Dimensions (L x W x H)</i>	1,46 x 1,45 x 1,42 m (with tilting but without hitch)
<i>Weight</i>	1120 kg (without hitch + options)
<i>Oil flow</i>	Flow : from 50 up to 150 l/min
<i>Main hydraulic pressure</i>	Pressure : from 270 up to 350 bar
<i>Oil flow</i>	Flow : from 36 up to 45 l/min
<i>Secondary hydraulic pressure</i>	Pressure : from 190 up to 250 bar (210 bar recommended)

### Standard equipment

- 4 hydraulic hoses without coupler, length 2 m + extension 0.50 m.
- Knife + counter-knife.

	Price	Reference
<b>MODEL</b>		
<b>XYLOCUT 310 PE</b> - For excavator	<b>19570.00</b>	78324A
<b>COUPLING HITCH &gt; OBLIGATORY TO DETERMINE + model to be defined before order</b>		
• Excavator with quick-fit coupling		See page 230-233
<b>OPTIONS</b>		
Accumulating clamp (with 2 hydraulic hoses without couplers)	<b>3635.00</b>	78325A
Hydraulic tilting +/- 90°. So 180° reach	<b>7815.00</b>	78326A
<b>SPARE PARTS</b>		
XYLOCUT 310 PE spare knife	<b>422.00</b>	783100