



XYLOGRIP 180 R with mini-excavator coupling



XYLOGRIP 230 R



XYLOGRIP 180 R on front loader



Rabaud advantages

- Two wood grips models adaptable to front loader, telescopic handler, forestry crane, mini-excavator...
- Front loader or telescopic loader coupling hitch with clamp support to prevent tipping during transport - RABAUD EXCLUSIVITY.
- 360° rotator in option.
- HLE steel clamps for extra strength.
- Thanks to the large opening of the clamp, you can take several pieces of wood or a bundle of 1 m³ (1 stère).

Technical characteristics

MODELS	XYLOGRIP 180	XYLOGRIP 230
<i>Coupling</i>	Excavator from 2.5 to 10 Tons, compact loader, crane, telescopic...	Excavator from 4.5 to 14 Tons, compact loader, crane, telescopic...
<i>Maximum weight</i>	1500 kg	2500 kg
<i>Dimensions of closed clamp (L x W x H)</i>	0,25 x 0,70 x 0,74 m	0,37 x 0,87 x 0,83 m
<i>Maximum opening of the clamp</i>	1,27 m	1,50 m
<i>Clamp surface</i>	0,18 m ²	0,23 m ²
<i>Grip weight</i>	Without rotator : 72 kg With rotator : 89 kg	Without rotator : 165 kg With rotator : 194 kg
<i>Working pressure</i>	175 bar	
<i>Clamping force (at end of clamp)</i>	14.2 kN at 200 bar	13.8 kN at 200 bar
<i>Maximum pressure</i>	200 bar	
<i>Oil flow</i>	40 L/min. recommended	



XYLOGRIP 180
with direct coupling hitch to mini-excavator



XYLOGRIP 230 R
with direct coupling hitch to mini-excavator



XYLOGRIP 230 R in transport position
with telescopic coupling hitch

				Price	Reference		
MODELS							
XYLOGRIP 180 2 hydraulic hoses without couplers				1850.00	78306A		
XYLOGRIP 180 R + ROTATOR 4 hydraulic hoses without couplers				2725.00	78301A		
XYLOGRIP 230 2 hydraulic hoses without couplers				2645.00	78338A		
XYLOGRIP 230 R + ROTATOR 4 hydraulic hoses without couplers				3350.00	78332A		
COUPLING HITCH + SHAFT OBLIGATORY TO DETERMINE				XYLOGRIP 180 - 230	XYLOGRIP 180 R - 230 R		
Mini excavator / Crane coupling hitch	direct by suspension hitch Arm width : 121 to 200 mm		•	•	500.00	78335A	
	by cardan suspension with 8-hole plate to be bolted to a quick coupling hitch (<i>Coupling hitch reference to be added, see pages 230-233</i>)	2-axes cardan shaft	•	•	560.00	76976A	
		cardan shaft with double swing brake		•	730.00	76975A	
Loader / Telescopic coupling hitch	with suspension bracket and hanging system		2-axes cardan shaft	•	•	1310.00	78352A
			cardan shaft with double swing brake		•	1485.00	78351A
OPTIONS							
6-way hydraulic valve	+ Electric reel with 15 m cable for telescopic mast lifting + rotator				1080.00	78302A	
	+ 12 m extension lead for mini excavator / crane / loader + rotator				785.00	78334A	
Non-return valve advised for telescopic Merlo, Bobcat, FDI-Sambron, Kubota skidsteer			for XYLOGRIP 180 and 180R		195.00	78314A	
			for XYLOGRIP 230 and 230R		215.00	78336A	

